



### Range Tuff Wear Parts

TASSCO is pleased to offer Range Tuff wear parts. The Range Tuff brand was developed with the harsh conditions of hard rock and surface mining in mind. Range Tuff wear parts are a composite material consisting of a chrome-moly white iron surface for very high wear resistance with a mild steel backing plate for ease of welding and forming. The mild steel backing plate allows the product to withstand light to moderate impact. The hardness of the Range Tuff product is 700 BHN. Ideal working temperatures of Range Tuff should not exceed 575 Deg F. Please contact TASSCO for cutting, welding, or forming instructions for the Range Tuff product line.

TASSCO P/N	SIZE
RT100	1" X 1" X 9.5" Chocky Bar
RT150	1" X 1.5" X 9.5" Chocky Bar
RT200	1" X 2" X 9.5" Chocky Bar
RT250	1" X 2.5" X 9.5" Chocky Bar
RT400	1" X 4" X 9.5" Chocky Bar
RTB03	3" Diameter Button
RTB04	4" Diameter Button
RTD01	4" OD X 2" ID Donut (Bolt Protector)
RTD02	4" OD X 2-3/4" ID Donut (Bolt Protector)
RTRB212	2" Diameter X 12" Long Roll Bar

### Custom Steel Fabricated Abrasion & Impact Resistant Solutions

TASSCO focuses on exceeding the expectations of our customers by offering value added solutions that reduce costs and lead times. Contact us to learn more about our TASSCO XT, TASSCO Comp-C, and TASSCO CORRHARD wear plate materials and custom fabrication capabilities.