
SCREW CONVEYOR AND TROUGH

FROM THE LOG DECK TO THE FUEL BIN

LUMBER & SAWMILLS

Wear plate, overlay and fabricated liners for every wear point from the log yard to the boiler fuel bin. We measure the part, match the grade to the zone, and build it in Birmingham.

WHAT TASSCO® BUILDS

Built off your spare set, or measured on the machine

01 Log yard and infeed

- Log deck and step feeder wear faces
- Unscrambler and infeed trough liners
- Chain conveyor wear strips

02 Debarking

- Debarker infeed and outfeed troughs
- Bark chutes
- Liners under the bark conveyor

03 Chipping and hogging

- Chipper feed spouts and chip chutes
- Transition pieces
- Hog housing and feed area liners

04 Pneumatic handling

- Blower and fan housing and blade liners
- Elbows and lift tubes off the chipper
- Ductwork transitions

05 Conveyors

- Drag chain conveyor floor liners
- Drag chain conveyor side liners
- Bark, slab, trim and waste conveyors

06 Screening, bins and fuel

- Chip screen chutes
- Chip and sawdust bin liners
- Truck loadout chutes

SHOP-BUILT, FIELD-PROVEN


Drag chain conveyor floor liner


XT bark scalping discs

PRODUCTS AND SOLUTIONS · SAWMILLS

RIGHT GRADE, RIGHT WEAR ZONE.

Every grade ships from stock as plate, cut to size, or fully fabricated.

FLAGSHIP GRADE · MELTED AND MADE IN USA

TASSCO XT

HARD FROM FACE TO CENTERLINE. CONSISTENT FROM HEAT TO HEAT.

XT is low-carbon, alloy-rich plate that's hard through its full thickness. Chromium, molybdenum and boron carry hardness to the core, nickel adds toughness, and your shop welds it with standard procedure.

477 BHN HARDNESS · 450–514	**.20–.23** % CARBON, ALLOY-RICH
3/16"–1" STOCKED THICKNESS	**170 ksi** YIELD, TYPICAL

FUSED ALLOY

Fusion-bonded CCO, smooth and bead-free

700 BHN · 2:1 VS WELDED CCO · ½"–1¼"

- Chip chutes and spouts
- Cyclone liners and cones

COMP-C

Welded chromium carbide overlay

60 HRC · 1L / 2L · 3/8"–1½"

- Hog housings and feed areas
- Drag conveyor floors

CORRHARD

Martensitic stainless, abrasion plus corrosion

314 BHN · 12% CR · 3/16"–1"

- Wet bark and chip handling
- Debarker troughs

RANGE TUFF

High-chrome white iron, weld-on

700 BHN · 4 FORMS · WELD-ON

- Loader bucket lips and edges
- Grapple wear points

HOW WE WORK

One supplier, one number to call

01 MEASURE
Off your spare set, off the machine, or with LiDAR scanning and DEM modeling.

02 DRAW
Grade, thickness, holes and bends. Kept on file for next time.

03 FABRICATE
Cut, formed, rolled, beveled and drilled in our Birmingham shop.

04 DELIVER
Marked and kitted for the change-out, ready to bolt up or weld in.

TALK TO A WEAR SPECIALIST

BRING A DRAWING, A WORN PART, OR A PHOTO.

We'll take it from there.

PHONE
205-949-2725

EMAIL
sales@tassco.com

TASSCO.COM